

USB 2.0 Docking Station 9/1 LAN + VGA



Specifications

- Compliant with USB2.0
- 1x DB15/M VGA in port combined with USB upstream interface
- 1x DB15/F VGA out port
- 3x USB2.0 A/F down stream ports
- 2x PS/2F ports for keyboard/mouse
- 1x RJ45 Ethernet LAN port
- 1x DB9/M serial port
- 1x DB25/F parallel port
- Compliant with IEEE 1284
- Over-current protection
- Supports OHCI/UHCI USB host controller
- Supports VGA up to 2048 x 1536 resolution
- Supports Windows 98 SE / ME / 2000 / XP
- Supports IEEE802.3x flow control function for 100 Base-Tx and 10 Base-T
- Supports bus power and self power
- Supports plug & play
- LED indicator for power on/off
- LED indicator for LAN link/active
- Dimensions: 236 x 58 x 28 mm
- Dimensions (packing box): 260 x 165 x 55 mm
- Weight: 0.215 kg
- Overall weight: 0.700 kg
- Operating temperature: 0°C - 70°C
- Storage temperature: 0°C - 85°C
- Humidity: 0% - 80% RH
- Reliability: MTBF > 25.000 h

Package Contents

- 1x USB2.0 Docking Station
- 1x USB/VGA Cable 0.7m
- 1x Switching Power Adapter 5V/2.0A
- 1x Driver CD with Manual

